

Test Report

No.: 64.190.25.4254.01-00

Dated: 2025-08-28



中国认可
国际互认
检测
TESTING
CNAS L3584



Applicant: OfficeWorldTrade
Address: Grossrietstrasse 2 8606 Nänikon Switzerland
Sample Submission: The samples were submitted by applicant and identified.
Product Name: Office Chair
Order No.: /
Identification/Style No.: 732519
Manufacturer: /
Country of Origin: /
Export to: /
Receipt Date of Sample: 2025-07-30
Date of Testing: From 2025-07-30 to 2025-08-20
Test Result: Refer to the data listed in following pages

Test Specification(s) or Test Item(s):

1. EN 1335-2:2018 Office furniture—Office work chair—Part 2: Safety requirements (Excluding Clause 4.4-2)

Conclusions:

Pass

Hardline Laboratory

TÜV SÜD Certification and Testing (China) Co., Ltd. Guangzhou Branch



Tested By: Knight Li
Knight Li
Test Engineer

Reviewed By: Rookie Wen
Rookie Wen
Designated Reviewer

Note:

- (1) The TÜV SÜD Certification and Testing (China) Co., Ltd. "General Terms & Conditions" applied.
Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question. It does not imply a general statement regarding the quality of products from regular production. For further details please see "Testing, Certification, Validation and Verification Regulations", chapter A-3.3.
For full version, please visit: EN : <https://www.tuvsud.cn/zh-cn/resource/terms-and-conditions---en> ; SCN: <https://www.tuvsud.cn/zh-cn/terms-and-conditions> ; TCN: <https://www.tuvsud.com/zh-tw/terms-and-conditions>
- (2) The results relate only to the items tested.
- (3) The test report shall not be reproduced except in full, without the written approval of the laboratory.

Laboratory:
B1/F. of Building A2, Building D1, No.63,
Chuangqi Road, Shilou, Panyu District,
Guangzhou, Guangdong, China 511447

Telephone : +86 20 3832 0668
Telefax : +86 20 3832 0478
<https://www.tuvsud.com>

Regd. Office:
TÜV SÜD Certification and Testing (China) Co.,
Ltd. Guangzhou Branch 5F, Communication
Building, 163 Pingyun Rd, Huangpu West Ave.
Guangzhou 510656P.R. China

Page 1 of 5

Description of the test subject:

1	Product Description	Office Chair
2	Dimensions / Weight	H x W x D (mm): 1120~1206 x 734 x 750 Weight (kg): 20.6
3	Intended use	Office use

Sample photo(s)



Sample preparation: the sample was stored in indoor ambient conditions for 24h

Test condition: 23°C 53%RH

Test Results:

1. EN 1335-2:2018 Office furniture—Office work chair—Part 2: Safety requirements (Excluding Clause 4.4-2)

Clause	Requirement -Test	Measuring result- Remark	Verdict
4	Safety requirements		/
4.1	General All parts of the chair with which the user comes into contact during intended use, shall be so designed that physical injury and damage to property are avoided.	This product complied with this item.	P
4.2	Shear and squeeze points		/
4.2.1	Shear and squeeze points under influence of powered mechanisms	Fulfilled	P
4.2.2	Shear and squeeze points during use	Fulfilled	P
4.3	Sequence of testing		/
4.4	Stability tests and requirements When tested according to the below test clause, the seating shall not overturn	See the below sub-clause	P
4.4-1	Corner stability (EN 1022:2018, 7.3.3)	Fulfilled	P
4.4-2	Forward overturning (EN 1022:2018, 7.3.1)		N/T
4.4-3	Forward overturning for chair with footrests (EN 1022:2018, 7.3.2)	No footrests	N/A
4.4-4	Sideways overturning for chairs without armrests (EN 1022:2018, 7.3.4)	With armrests	N/A
4.4-5	Sideways overturning for chairs with armrests (EN 1022:2018, 7.3.5.1 and 7.3.5.2)	Fulfilled	P
4.4-6	Rearwards overturning for chairs without back rest inclination and for chairs with adjustable backrest inclination that can be locked (EN 1022:2018, 7.3.6)	Fulfilled	P
4.4-7	Rearwards overturning for chairs with back rest inclination (EN 1022:2018, 7.4)	Fulfilled	P
4.5	Structural safety requirements	Refer to clause 5.2	P
5	Strength and durability	See the below sub-clause	/
5.1	General	See the below sub-clause	/

Clause	Requirement -Test	Measuring result- Remark	Verdict
5.1-1	Combined seat and back static load test (EN 1728:2012, 7.3)	Seat force F1: 1600 N Back rest force F2: 560 N Cycles: 10	P
5.1-2	Seat front edge static load test (EN 1728:2012, 7.4)	Seat force: 1600 N Cycles: 10	P
5.1-3	Foot rest static load test (EN 1728:2012, 7.8)	Force: 1300 N Cycles: 10	N/A
5.1-4	Seat and back durability (EN 1728:2012, 7.9)	Step 1: Force: 1500 N, at point A Cycles: 120000	P
		Step 2: Force: 1200 N, at point C Force: 320 N, at point B Cycles: 80000	P
		Step 3: Force: 1200 N, at point J Force: 320 N, at point E Cycles: 20000	P
		Step 4: Force: 1200 N, at point F Force: 320 N, at point H Cycles: 20000	P
		Step 5: Force: 1100 N, at point D and G Cycles: 20000	P
5.1-5	Armrests durability (EN 1728:2012, 7.10)	Force: 400 N Cycles: 60000	P
5.1-6.1	Armrest downward static load test – central (before stability test) (EN 1728:2012, 7.5)	Force: 750 N Cycles: 5	P
5.1-6.2	Armrest downward static load test – central (after stability test) (EN 1728:2012, 7.5)	Force: 900 N Cycles: 5	P
5.2	Requirements The strength and durability requirements are fulfilled when, after testing in accordance with Table 2: a) there are no fractures of any member, joint or component; b) there is no loosening of joints intended to be rigid; and c) the chair fulfils its functions after removal of the test loads.	No fractures of any part. No loosening of joints. No function loss.	P
5.3	Rolling resistance test and requirements	Push force=17 N	P



Clause	Requirement -Test	Measuring result- Remark	Verdict
	After test: a). The castors shall be of identical construction b). The rolling resistance shall be ≥ 12 N.		
6	Information for use	Fulfilled.	P
Annex A	Loads, masses and cycles for functional tests - Suggested loads, masses and cycles		
A.1	Arm rest downward static load test – front	Force: 450 N Cycles: 5	P
A.2	Arm rest sideways static load test	Force: 400 N Cycles: 10	P
A.3	Swivel test	Masse M1: 60 kg Masse M2: 35 kg Cycles: 120000	P
A.4	Foot rest durability	Force: 900 N Cycles: 50000	N/A
A.5	Castor and chair base durability	Masse M1: 110 kg Cycles: 36000	P

Abbreviation: P=Pass; F=Fail; N/A = Not Applicable; N/T=Not Tested.

Remark:

1. The test results exclusively based on the submitted samples.
2. Clause(s) with the symbol “/” in the result refers to the result(s) of this sub-clause(s).
3. This report extracts from test report No. 64.190.25.4036.01-00, issued on 2025-08-20. Only update the applicant's name, address and Style No. information.
4. Specific requirement of test report as per clause 7.8.3 of CNAS-CL01-2018 or other accreditation scheme, such as: remark of subcontract information or on-site testing information.

Disclaimer Measurement Uncertainty:

Unless otherwise agreed upon, Pass or Fail verdicts are given based on the measured values without any considerations of measurement uncertainties.

Please note, every test method has a measurement uncertainty which has been evaluated by the laboratory according to ISO/IEC 17025 requirements.

By taking measurement uncertainties into account it might happen that measured values can neither be assessed as PASS nor as FAIL.

-End of Test Report-