

tone USB 3.0

Specifications

Rev. 1.2

Interface	USB 3.0								
Power Supply	USB bus-powered: DC 5V +/- 0.5V								
Power Consumption	Suspend Current < 500 μ A Operating Current max. 250mA								
Performance	Read: up to 90 MB/sec. Write: up to 30 MB/sec. <i>Speed depends on used flash modules and may vary.</i>								
Model Code / Size	<table><thead><tr><th>EAN Code</th><th>Size</th></tr></thead><tbody><tr><td>7640111166559</td><td>64GB</td></tr><tr><td>7640111166566</td><td>128GB</td></tr><tr><td>7640111166665</td><td>256GB</td></tr></tbody></table>	EAN Code	Size	7640111166559	64GB	7640111166566	128GB	7640111166665	256GB
EAN Code	Size								
7640111166559	64GB								
7640111166566	128GB								
7640111166665	256GB								
Flash Type	MLC,TLC								
Dimensions (LxWxH)	53*21.5*9.6mm								
Weight									
Operating Systems	Without Driver: Windows 10 Windows 8 Windows 7 Windows Vista Windows XP Windows 2003 Windows 2000 MAC OS 9 and higher Linux 2.6.x								
Environmental Conditions	Device in operation: 0 °C to 70 °C not in operation/storage: -25 °C to 85 °C								
Service/Warranty	2 year full warranty								
Certifications and Standard Compliance	CE, FCC, RoHS								