

Yellow Label Standard PEFC™

Product Description Yellow Label Standard is a quality paper with a great whiteness that ensures sharp text contrasts. The paper is made using modern filler and fibre technology. This ensures a homogeneous composition and provides outstanding value for everyday use.

Properties	Grammage	80
	[g/m ²]	
	ISO 536	
	Thickness	104
	[µm]	
	ISO 534	
	Bulk	1.30
	[cm ³ /g]	
	ISO 534	
	Whiteness	150
	CIE	
	ISO 11475	
	Opacity	93.5
	[%]	
	ISO 2471	
	Brightness	105
	D65	
	ISO 2470-2	

Features	Yellow Label Standard provides high quality in a wide range of applications, including daily communication: emails, faxes and reports.
Size	This media is available in the following size(s) and grain direction • A4 [210×297 mm] with Long Grain • A3 [297×420 mm] with Short Grain
Storage	Temperature 10 - 30 °C, Relative Humidity 20 - 70% Repack opened reams or boxes when not in use.
Print	Acclimatize paper 24 hours before printing in print room conditions (preferably next to printer) Best results are obtained between 15-25 °C and 30-65% RH (relative humidity)
Environment, Health & Safety	No Material Safety Data Sheet required. ISO 9001 and 14001 certified production site. ECF (Elemental Chlorine Free) bleaching technique for wood pulp. Acid- lignin- and sulphur-free paper with a high degree of permanence, ISO9706 Permanent Paper certified. Paper waste is suitable for recycling in most countries. Please refer to local paper recycle station.

Environmental Certification



Disclaimer

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

This document was last edited on: Tuesday, March 18, 2025

Canon Inc.

canon.com

Canon Europe

canon-europe.com

English edition