

Trade name: edding Porcelain marker ink (green) contained in: edding 4200

Current version : 4.0.1, issued: 27.10.2022

Replaced version: 4.0.0, issued: 05.08.2020

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding Porcelain marker ink (green) contained in: edding 4200

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Ink for use in felt pens

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Skin Sens. 1; H317

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS07

Signal word

Warning

Hazardous component(s) to be indicated on label:

1,2-benzisothiazol-3(2H)-one

Hazard statement(s)

H317

May cause an allergic skin reaction.

Hazard statements (EU)

Trade name: edding Porcelain marker ink (green) contained in: edding 4200

Current version : 4.0.1, issued: 27.10.2022

Replaced version: 4.0.0, issued: 05.08.2020

Region: GB

EUH208

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1). May produce an allergic reaction.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients
3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures
Chemical characterization

Mixture (preparation)

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration
			%
1	ethanediol		
	107-21-1 203-473-3 603-027-00-1 -	Acute Tox. 4*; H302	< 2.50 wt%
2	ethanediol		
	107-21-1 203-473-3 603-027-00-1 01-2119456816-28	Acute Tox. 4; H302 STOT RE 2; H373o	< 2.50 wt%
3	ammonia		
	1336-21-6 215-647-6 007-001-01-2 -	Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Acute 1; H400	< 0.50 wt%
4	ammonia		
	1336-21-6 215-647-6 007-001-01-2 01-2119488876-14	Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Acute 1; H400	< 0.50 wt%
5	1,2-benzisothiazol-3(2H)-one		
	2634-33-5 220-120-9 613-088-00-6 -	Acute Tox. 4*; H302 Aquatic Acute 1; H400 Eye Dam. 1; H318 Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 0.05 - < 1.00 wt%
6	1,2-benzisothiazol-3(2H)-one		
	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Aquatic Acute 1; H400 Eye Dam. 1; H318 Skin Irrit. 2; H315 Skin Sens. 1; H317	< 0.10 wt%
7	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1)		

Trade name: edding Porcelain marker ink (green) contained in: edding 4200

Current version : 4.0.1, issued: 27.10.2022

Replaced version: 4.0.0, issued: 05.08.2020

Region: GB

	55965-84-9 - 613-167-00-5 -	Acute Tox. 2; H310 Acute Tox. 2; H330 Acute Tox. 3; H301 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 Eye Dam. 1; H318 Skin Corr. 1C; H314 Skin Sens. 1A; H317	< 0.0015	wt%
8	glycerol			
	56-81-5 200-289-5 - -	-	< 5.00	wt%
9	Tetrabenzo-5,10,15,20-diazaporphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3)			
	147-14-8 205-685-1 - -	-	< 5.00	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(*, **, ***, ****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
3	B	STOT SE 3; H335: C ≥ 5%	-	-
4	B	STOT SE 3; H335: C ≥ 5%	-	-
5	-	Skin Sens. 1; H317: C ≥ 0.05%	-	-
6	-	Skin Sens. 1; H317: C ≥ 0.05%	M = 10	-
7	B	Skin Sens. 1A; H317: C ≥ 0.0015% Eye Irrit. 2; H319: C ≥ 0.06% Skin Irrit. 2; H315: C ≥ 0.06% Skin Corr. 1C; H314: C ≥ 0.6% Eye Dam. 1; H318: C ≥ 0.6%	M = 100	M = 100

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
2	H373 oral; kidneys; -

Acute toxicity estimate (ATE) values			
No	oral	dermal	inhalative
4	350 mg/kg bodyweight		

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

Trade name: edding Porcelain marker ink (green) contained in: edding 4200**Current version :** 4.0.1, issued: 27.10.2022**Replaced version:** 4.0.0, issued: 05.08.2020**Region:** GB**After ingestion**

Rinse the mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Trade name: edding Porcelain marker ink (green) contained in: edding 4200

Current version : 4.0.1, issued: 27.10.2022

Replaced version: 4.0.0, issued: 05.08.2020

Region: GB

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	glycerol	56-81-5	200-289-5
List of approved workplace exposure limits (WELs) / EH40			
	Glycerol mist		
	WEL long-term (8-hr TWA reference period)	10	mg/m ³
2	Tetrabenzo-5,10,15,20-diazaporphyrinephthalocyanine (C.I.Pigment #74160 Blue 15:3)	147-14-8	205-685-1
List of approved workplace exposure limits (WELs) / EH40			
	Copper and compounds (as Cu) dusts and mists		
	WEL short-term (15 min reference period)	2	mg/m ³
	WEL long-term (8-hr TWA reference period)	1	mg/m ³
3	ethanediol	107-21-1	203-473-3
2000/39/EC			
	Ethylene glycol		
	WEL short-term (15 min reference period)	104	mg/m ³ 40 ppm
	WEL long-term (8-hr TWA reference period)	52	mg/m ³ 20 ppm
	Skin resorption / sensibilisation	Skin	
List of approved workplace exposure limits (WELs) / EH40			
	Ethane-1,2-diol vapour		
	WEL short-term (15 min reference period)	104	mg/m ³ 40 ppm
	WEL long-term (8-hr TWA reference period)	52	mg/m ³ 20 ppm
	Comments	Sk	
List of approved workplace exposure limits (WELs) / EH40			
	Ethane-1,2-diol particulate		
	WEL long-term (8-hr TWA reference period)	10	mg/m ³
	Comments	Sk	
4	ethanediol	107-21-1	203-473-3
2000/39/EC			
	Ethylene glycol		
	WEL short-term (15 min reference period)	104	mg/m ³ 40 ppm
	WEL long-term (8-hr TWA reference period)	52	mg/m ³ 20 ppm
	Skin resorption / sensibilisation	Skin	
List of approved workplace exposure limits (WELs) / EH40			
	Ethane-1,2-diol vapour		
	WEL short-term (15 min reference period)	104	mg/m ³ 40 ppm
	WEL long-term (8-hr TWA reference period)	52	mg/m ³ 20 ppm
	Comments	Sk	
List of approved workplace exposure limits (WELs) / EH40			
	Ethane-1,2-diol particulate		
	WEL long-term (8-hr TWA reference period)	10	mg/m ³
	Comments	Sk	

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name	CAS / EC no
	Route of exposure	Value
	Exposure time	
	Effect	
1	ethanediol	107-21-1 203-473-3
	dermal	Long term (chronic) systemic 106 mg/kg/day

Trade name: edding Porcelain marker ink (green) contained in: edding 4200

Current version : 4.0.1, issued: 27.10.2022

Replaced version: 4.0.0, issued: 05.08.2020

Region: GB

2	inhalative	Long term (chronic)	local	35	mg/m ³
	ammonia			1336-21-6 215-647-6	
	dermal	Short term (acut)	systemic	6.8	mg/kg/day
	with reference to: CAS 7664-41-7				
	dermal	Long term (chronic)	systemic	6.8	mg/kg/day
	with reference to: CAS 7664-41-7				
	inhalative	Short term (acut)	systemic	47.6	mg/m ³
	with reference to: CAS 7664-41-7				
	inhalative	Short term (acut)	local	36	mg/m ³
	with reference to: CAS 7664-41-7				
	inhalative	Long term (chronic)	systemic	47.6	mg/m ³
	with reference to: CAS 7664-41-7				
	inhalative	Long term (chronic)	local	14	mg/m ³
	with reference to: CAS 7664-41-7				

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	ethanediol			107-21-1 203-473-3	
	dermal	Long term (chronic)	systemic	53	mg/kg/day
	inhalative	Long term (chronic)	local	7	mg/m ³
2	ammonia			1336-21-6 215-647-6	
	oral	Short term (acut)	systemic	6.8	mg/kg/day
	with reference to: CAS 7664-41-7				
	oral	Long term (chronic)	systemic	6.8	mg/kg/day
	with reference to: CAS 7664-41-7				
	dermal	Short term (acut)	systemic	68	mg/kg/day
	with reference to: CAS 7664-41-7				
	dermal	Long term (chronic)	systemic	68	mg/kg/day
	with reference to: CAS 7664-41-7				
	inhalative	Short term (acut)	systemic	23.8	mg/m ³
	with reference to: CAS 7664-41-7				
	inhalative	Short term (acut)	local	7.2	mg/m ³
	with reference to: CAS 7664-41-7				
	inhalative	Long term (chronic)	systemic	23.8	mg/m ³
	with reference to: CAS 7664-41-7				
	inhalative	Long term (chronic)	local	2.8	mg/m ³
	with reference to: CAS 7664-41-7				

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	ethanediol		107-21-1 203-473-3	
	water	fresh water	10	mg/L
	water	marine water	1	mg/L
	water	Aqua intermittent	10	mg/L
	water	fresh water sediment	37	mg/kg dry weight
	water	marine water sediment	3.7	mg/kg dry weight
	soil	-	1.53	mg/kg dry weight
	sewage treatment plant	-	199.5	mg/L
2	ammonia		1336-21-6 215-647-6	
	water	fresh water	0.0011	mg/L
	with reference to: CAS: 7664-41-7			

Trade name: edding Porcelain marker ink (green) contained in: edding 4200

Current version : 4.0.1, issued: 27.10.2022

Replaced version: 4.0.0, issued: 05.08.2020

Region: GB

	water	marine water	0.0011	mg/L
	with reference to: CAS: 7664-41-7			
	water	Aqua intermittent	0.0068	mg/L
	with reference to: CAS: 7664-41-7			

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation
liquid
Form
liquid
Colour
green
Odour
characteristic
pH value
No data available
Boiling point / boiling range
No data available
Melting point/freezing point
No data available
Decomposition temperature
No data available
Flash point
No data available
Ignition temperature
No data available
Flammability
No data available

Trade name: edding Porcelain marker ink (green) contained in: edding 4200

Current version : 4.0.1, issued: 27.10.2022

Replaced version: 4.0.0, issued: 05.08.2020

Region: GB

Lower explosion limit

No data available

Upper explosion limit

No data available

Vapour pressure

No data available

Relative vapour density

No data available

Relative density

No data available

Density

No data available

Solubility

No data available

Partition coefficient n-octanol/water (log value)

No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
	log Pow	-1.36	
	Reference temperature	25	°C
	Source	ECHA	

Kinematic viscosity

No data available

Particle characteristics

No data available

9.2 Other information
Other information

No data available.

SECTION 10: Stability and reactivity
10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

No data available.

SECTION 11: Toxicological information
11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	edding Porcelain marker ink (green) contained in: edding 4200

Trade name: edding Porcelain marker ink (green) contained in: edding 4200

Current version : 4.0.1, issued: 27.10.2022

Replaced version: 4.0.0, issued: 05.08.2020

Region: GB

Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).
----------	---

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
LD50		5840	mg/kg bodyweight
Species	rat		
Source	Manufacturer		
2	ammonia	1336-21-6	215-647-6
LD50		350	mg/kg bodyweight
Species	rat		
with reference to	CAS 7664-41-7		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
LD50		9530	mg/kg bodyweight
Species	rabbit		
Source	Manufacturer		

Acute inhalational toxicity			
No data available			

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
Duration of exposure		20	h
Species	rabbit		
Source	ECHA		
Evaluation	non-irritant		
2	ammonia	1336-21-6	215-647-6
Duration of exposure		4	h
Species	rabbit		
with reference to	CAS 7664-41-7		
Method	OECD 404		
Source	ECHA		
Evaluation	corrosive		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
Duration of exposure		24	h
Species	rabbit		
Source	ECHA		
Evaluation	non-irritant		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
Route of exposure	Skin		
Species	guinea pig		
Source	ECHA		
Evaluation	non-sensitizing		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
Type of examination	Bacterial Reverse Mutation Test		

Trade name: edding Porcelain marker ink (green) contained in: edding 4200

Current version : 4.0.1, issued: 27.10.2022

Replaced version: 4.0.0, issued: 05.08.2020

Region: GB

Species	Salmonella typhimurium: TA 1535, TA 1537, TA 98, TA 100; Escherichia coli WP2 uvrA
Method	OECD 471
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
2	ammonia
	1336-21-6
	215-647-6
Duration of exposure	48 h
Type of examination	Bacterial Reverse Mutation Test
Species	Salmonella typhimurium TA98, TA100, TA1535, TA1537
with reference to	CAS 7664-41-7
Method	OECD 471
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

STOT - single exposure			
No data available			

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
Route of exposure	oral		
NOAEL		150	mg/kg bw/d
Duration of exposure		12	months
Species	rat		
Target organ	kidneys		
Method	OECD 452		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are met.		

Aspiration hazard			
No data available			

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
LC50		>	72860 mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Source	ECHA		

Toxicity to fish (chronic)			
----------------------------	--	--	--

Trade name: edding Porcelain marker ink (green) contained in: edding 4200

Current version : 4.0.1, issued: 27.10.2022

Replaced version: 4.0.0, issued: 05.08.2020

Region: GB

No data available

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
EC50	>	100	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No data available			

Toxicity to algae (acute)			
No data available			

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No data available			

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
Type	DOC decrease		
Value	90	- 100	%
Duration		10	day(s)
Method	OECD 301 A		
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	ethanediol	107-21-1	203-473-3
log Pow		-1.36	
Reference temperature		25	°C
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information	
Do not discharge product unmonitored into the environment.	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Trade name: edding Porcelain marker ink (green) contained in: edding 4200

Current version : 4.0.1, issued: 27.10.2022

Replaced version: 4.0.0, issued: 05.08.2020

Region: GB

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information
14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulations
Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	75
2	1,2-benzisothiazol-3(2H)-one	2634-33-5	220-120-9	75
3	ammonia	1336-21-6	215-647-6	75
4	ammonia	1336-21-6	215-647-6	75
5	potassium hydroxide	1310-58-3	215-181-3	75
6	propan-2-ol	67-63-0	200-661-7	75
7	propan-2-ol	67-63-0	200-661-7	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

Trade name: edding Porcelain marker ink (green) contained in: edding 4200**Current version :** 4.0.1, issued: 27.10.2022**Replaced version:** 4.0.0, issued: 05.08.2020**Region:** GB**SECTION 16: Other information****Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH071	Corrosive to the respiratory tract.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H373o	May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

B	Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.
---	---

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 636503