Trade name: Marabu-Fixogum 125 g Tube

Version: 5 / GB Date revised: 17.05.2017

Substance number: 290117000 Replaces Version: 4 / GB Print date: 19.05.17

# <u>SECTION 1: Identification of the substance/mixture and of the company/undertaking</u>

# 1.1. Product identifier

Marabu-Fixogum 125 g Tube

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Use of the substance/preparation

Adhesive agent

# **Identified Uses**

PC1 Adhesives, sealants

SU22 Professional uses: Public domain (administration, education, entertainment,

services, craftsmen)

SU21 Consumer uses: Private households (= general public = consumers)

#### **Uses advised against**

SU0 Other

# 1.3. Details of the supplier of the safety data sheet

#### **Address**

Marabu GmbH & Co. KG Asperger Strasse 4 71732 Tamm Germany

Telephone no. +49-7141/691-0 Fax no. +49-7141/691-147

Information provided Department product safety

by / telephone

E-mail address of PRSI@marabu.de

person responsible for this SDS

# 1.4. Emergency telephone number

(+49) (0)621-60-43333

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411

#### 2.2. Label elements

# Labelling according to regulation (EC) No 1272/2008

## **Hazard pictograms**



Trade name: Marabu-Fixogum 125 g Tube

Version: 5 / GB Date revised: 17.05.2017

Substance number: 290117000 Replaces Version: 4 / GB Print date: 19.05.17

# Signal word

Danger

#### **Hazard statements**

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H225 Highly flammable liquid and vapour.

# **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P264.1 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P405 Store locked up.

P501.9 Dispose of contents/container as problematic waste.

# Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

# 2.3. Other hazards

No special hazards have to be mentioned.

# SECTION 3: Composition/information on ingredients \*\*\*

# 3.2. Mixtures

# **Chemical characterization**

Adhesive agent based on natural caoutchouc and on solvents

## Hazardous ingredients \*\*\*

## Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

CAS No. 64742-49-0 EINECS no. 921-024-6

Registration no. 01-2119475514-35

Concentration >= 50 < 100 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H225 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aguatic Chronic 2 H411

# ${\bf 6,6'\text{-}di\text{-}tert\text{-}butyl\text{--}2,2'\text{-}methylenedi\text{-}p\text{-}cresol}$

CAS No. 119-47-1 EINECS no. 204-327-1

Concentration >= 0,1 < 1%

Classification (Regulation (EC) No. 1272/2008)

Repr. 2 H361 Route of exposure: oral

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

Trade name: Marabu-Fixogum 125 g Tube

Version: 5 / GB Date revised: 17.05.2017

Substance number: 290117000 Replaces Version: 4 / GB Print date: 19.05.17

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

# 4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

# 4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / treatment

Treat symptomatically

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

# Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist, Not be used for safety reasons: water jet

#### 5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); dense black smoke

#### 5.3. Advice for firefighters

### Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

#### 6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

#### 6.4. Reference to other sections

Trade name: Marabu-Fixogum 125 g Tube

Version: 5 / GB Date revised: 17.05.2017

Substance number: 290117000 Replaces Version: 4 / GB Print date: 19.05.17

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

## Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

# Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires B (Combustible liquid substances)

Temperature class T4

# 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

## Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

# Storage class according to TRGS 510

Storage class according to 3 Flammable liquid

**TRGS 510** 

#### Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

# 7.3. Specific end use(s)

Adhesive agent

# SECTION 8: Exposure controls/personal protection \*\*\*

# 8.1. Control parameters

#### **Derived No/Minimal Effect Levels (DNEL/DMEL)**

# Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Trade name: Marabu-Fixogum 125 g Tube

Version: 5 / GB Date revised: 17.05.2017

Substance number: 290117000 Replaces Version: 4 / GB Print date: 19.05.17

Mode of action Systemic effects

Concentration 699 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 773 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 699 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 2035 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consumer

Long term
inhalative

Systemic effects

Concentration 608 mg/m<sup>3</sup>

#### 8.2. Exposure controls

#### **Exposure controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

#### Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

#### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

#### Eye protection

Trade name: Marabu-Fixogum 125 g Tube

Version: 5 / GB Date revised: 17.05.2017

Substance number: 290117000 Replaces Version: 4 / GB Print date: 19.05.17

Use safety eyewear designed to protect against splash of liquids.

# **Body protection**

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

**Form** Pasty

Colourcolourless, clearOdourpetrol-like

**Odour threshold** 

Remarks No data available

pH value

Remarks Not applicable

**Melting point** 

Remarks not determined

Freezing point

Remarks not determined

Initial boiling point and boiling range

Value appr. 84 °C

Pressure 1.013 hPa

Source Literature value

Flash point

Value -18 °C

Method DIN 53213

**Evaporation rate (ether = 1):** 

Remarks not determined

Flammability (solid, gas)

Not applicable

Upper/lower flammability or explosive limits

Lower explosion limit appr. 0,6 %(V) Upper explosion limit appr. 7 %(V)

Source Literature value

Vapour pressure

Value appr. 60 hPa

Method Value taken from the literature

Vapour density

Remarks not determined

**Density** 

Value 0,72 g/cm<sup>3</sup>

Solubility in water

Remarks partially miscible

Partition coefficient: n-octanol/water

Remarks Not applicable

Ignition temperature

Value appr. 200 °C

Source Literature value

**Viscosity** 

Trade name: Marabu-Fixogum 125 g Tube

Version: 5 / GB Date revised: 17.05.2017

Substance number: 290117000 Replaces Version: 4 / GB Print date: 19.05.17

dynamic

Value 7500 mPa.s

Temperature 20 °C

Method Brookfield

kinematic

Value > 20,6 mm<sup>2</sup>/s

Temperature 40 °C

Efflux time

Remarks not determined

**Explosive properties** 

evaluation no

**Oxidising properties** 

evaluation None known

#### 9.2. Other information

#### Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

# SECTION 10: Stability and reactivity

# 10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

#### 10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

#### 10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

### 10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

#### 10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

# Acute oral toxicity

Remarks Based on available data, the classification criteria are not met.

#### **Acute oral toxicity (Components)**

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Species rat

LD50 > 5000 mg/kg

### Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

# **Acute dermal toxicity (Components)**

# Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Species rabbit

LD50 > 2000 mg/kg

Trade name: Marabu-Fixogum 125 g Tube

Version: 5 / GB Date revised: 17.05.2017

Substance number: 290117000 Replaces Version: 4 / GB Print date: 19.05.17

#### Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

#### **Acute inhalative toxicity (Components)**

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Species rat

LC50 > 20 mg/l

Administration/Form Vapors

#### Skin corrosion/irritation

evaluation irritant

Remarks The classification criteria are met.

#### Serious eye damage/irritation

Remarks Based on available data, the classification criteria are not met.

**Sensitization** 

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

## **Specific Target Organ Toxicity (STOT)**

Single exposure

Remarks The classification criteria are met. evaluation May cause drowsiness or dizziness.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Experience in practice**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Other information

There are no data available on the mixture itself.

The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

#### **General information**

There are no data available on the mixture itself.Do not allow to enter drains or water courses.The

Trade name: Marabu-Fixogum 125 g Tube

Version: 5 / GB Date revised: 17.05.2017

Substance number: 290117000 Replaces Version: 4 / GB Print date: 19.05.17

mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

# Fish toxicity (Components)

# Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Species rainbow trout (Oncorhynchus mykiss)
LL50 11.4 mg/l

Duration of exposure 96 h

# 12.2. Persistence and degradability

#### **General information**

No data available

# 12.3. Bioaccumulative potential

#### **General information**

There are no data available on the mixture itself.

#### Partition coefficient: n-octanol/water

Remarks Not applicable

#### 12.4. Mobility in soil

#### **General information**

There are no data available on the mixture itself.

# 12.5. Results of PBT and vPvB assessment

#### **General information**

There are no data available on the mixture itself.

# 12.6. Other adverse effects

#### **General information**

There are no data available on the mixture itself.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

# Disposal recommendations for the product

Dispose according to legislation.

EWC waste code 08 04 09\* waste adhesives and sealants containing organic solvents

or other dangerous substances

# Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

# **SECTION 14: Transport information**

# Land transport ADR/RID

14.1. UN number

UN 1133

# 14.2. UN proper shipping name

ADHESIVES

# 14.3. Transport hazard class(es)

Class 3 Label 3

14.4. Packing group

Trade name: Marabu-Fixogum 125 g Tube

Version: 5 / GB Date revised: 17.05.2017

Substance number: 290117000 Replaces Version: 4 / GB Print date: 19.05.17

Packing group II
Special provision 640D
Limited Quantity 5 I
Transport category 3

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS
Tunnel restriction code D/E

# Marine transport IMDG/GGVSee

14.1. UN number

UN 1133

14.2. UN proper shipping name

**ADHESIVES** 

14.3. Transport hazard class(es)

Class 3

14.4. Packing group

Packing group II

14.5. Environmental hazards

Marine Pollutant

#### Air transport ICAO/IATA

**14.1. UN number** 

**UN 1133** 

14.2. UN proper shipping name

**ADHESIVES** 

14.3. Transport hazard class(es)

Class 3

14.4. Packing group

Packing group

14.5. Environmental hazards

**ENVIRONMENTALLY HAZARDOUS** 

#### Information for all modes of transport

#### 14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

nc

# SECTION 15: Regulatory information \*\*\*

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Major-accident categories acc. 96/82/EC

Category 9.II Dangerous for environment 200.000 kg 500.000 kg Category 7B Highly flammable liquids 5.000.000 kg 50.000.000 kg

**VOC** \*\*\*

VOC (EU) 90 %

VOC (EU) 648 g/l

#### Other information \*\*\*

The product does not contain substances of very high concern (SVHC).

## Other information

All components are contained in the TSCA inventory or exempted.

Trade name: Marabu-Fixogum 125 g Tube

Version: 5 / GB Date revised: 17.05.2017

Substance number: 290117000 Replaces Version: 4 / GB Print date: 19.05.17

All components are contained in the IECSC inventory.

#### 15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

# Hazard statements listed in Chapter 3

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H411 Toxic to aquatic life with long lasting effects.

#### CLP categories listed in Chapter 3

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic, Category 2

Asp. Tox. 1 Aspiration hazard, Category 1
Flam. Liq. 3 Flammable liquid, Category 3
Repr. 2 Reproductive toxicity, Category 2

Skin Irrit. 2 Skin irritation, Category 2

STOT SE 3 Specific target organ toxicity - single exposure, Category 3

#### Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\* This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship. The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.